

### Overview

This option provides the capability and corresponding software screens to create scenarios of multiple targets and messages. These can be transmitted on up to three different frequencies: 1090 MHz, 1030 MHz and 978 MHz. This allows the user to create scenarios with targets from each frequency band, to test that the multi-receiver can simultaneously receive these messages. The UAT and 1090 messages will be transmitted on the top and bottom ports. The 1030 messages will be transmitted on the selected port.

This option requires that the Transponder Option (RGSNGOPT10) has been purchased and installed on the RGS-2000NG.

### Description of Multi-Receiver Test Screens

#### Measurement Screen

- Two channel oscilloscope screen with trigger and port selections available

#### Own Aircraft Screen

- Settings available include: Mode S Address; Latitude; Longitude; Altitude; Heading

#### RTCA/DO-260 Test Screen (Option)

- See DO-260B MOPS Test Option (RGSNGOPT15) Product Description, document p/n 1025PD-OPT15.

#### Receiver Screen

- Indicators display types of messages being received. Messages can be captured, displayed, and logged in a data file.

### Scenario Screen

- *Gives user ability to create scenarios and setup:*
  - Scenario duration
  - 1090 MHz ADS-B dynamic and static targets
  - 1030 MHz ground station and TCAS messages
  - 978 MHz UAT dynamic and static targets
  - Initial MSO for dynamic and static
  - Dynamic and static UAT enable
  - MSO step dynamic and static UAT
- *Additional Scenario settings:*
  - Capture squitters and data logging
  - Static test mode
  - Slant range
  - Re-compile after load
  - Power mode
  - UAT I/Q filter magnitude
  - UAT horizontal spacing

For further information please contact:

**Cobham AvComm**  
10200 West York Street  
Wichita, KS 67215-8935 [USA]  
Phone: (316) 522-4981  
Fax: (316) 524-2623  
AvComm.TechSales@cobham.com

or contact your Cobham AvComm  
sales office