

# CSM 2.0 - Inline Cable Stripping Machine

Gentle stripping of cables – without damaging the inner construction

Product No.: 402.0005.05



## Technical Details:

<b>Size</b> (width x length x height)	1200 × 800 × 1250 mm 47.24 x 31.5 x 49.21 Inch
<b>Weight</b>	134 kg / 295 lbs 165 kg / 364 lbs incl. packaging
<b>Material</b>	Aluminium, stainless steel, PVC
<b>Supply voltage</b>	230 V / 50 - 60 Hz
<b>Input Power</b>	max. 750 W
<b>Cable diameter</b>	6 - 50 mm 0.27 - 1.97 Inch (flexible cable)
<b>Thickness of insulating layer</b>	0,2 - 5 mm 0.08 - 0.2 Inch (depending on hardness of the material)
<b>Speed</b>	max. 20 m / min max. 790 Inch per minute
<b>Appropriate materials</b>	PVC, PU, PE, LDPE, HDPE, FRNC, LSNH

*Efficiency, material and cost savings combined: Remove faulty cable sheaths - without damaging the cost-intensive inner construction, such as shielding braids - CSM 2.0*

## Device details:

- Motorized device for removing extruded sheaths
- No damage to underlying materials (shielding braid, tape, cores, wires, etc.)
- Easy positioning between winding and unwinding systems
- Reproducible and easily adjustable working depth of the blade
- Signal light as status display
- Emergency stop function for winding and unwinding systems possible via control circuit
- Automatic synchronization of the haul-off speed
- High operational stability thanks to robust construction

## Optional:

- Safety cage to seal off the system

